

IRRIGATION LEGEND

PRODUCT DESCRIPTION
HUNTER 1-40-04-SS-ON-B-XX/1-40-06-SS-B-XX, NOZZLE AS SHOWN
HUNTER 1-40-04-SS-B-XX/1-40-06-SS-B-XX, NOZZLE AS SHOWN
NOZZLE PERFORMANCE:

#15 @ 5.5 Bars - 68.9 l/min 18.0m RADIUS
#20 @ 5.5 Bars - 84.7 l/min 20.1m RADIUS

HUNTER (CV/IBV ELECTRIC COUTROL LALVE SIZE AS SHOWN

HUNTER HC-44-XX-AW QUICK COUPLER VALVE (OPTIONAL)

HUNTER IC-1200-M SOLID STATE METAL CABINET CONTROLLER
HUNTER SOLAR-SYNC-SEN ON SITE WEATHER SENSOR

HUNTER SOLAR-SYNC-SEN ON SITE WEATHER SENSOR

BY BACKFLOW PREVENTER SIZED TO SYSTEM l/min

BY BACKFLOW PREVENTER SIZED TO SYSTEM l/min

HANNLINE PIPE

LATERAL PIPE

i □⊠⊠⊅∙æ

ISOLATION VALVE LINE SIZED SLEEVING

SWING JOINTS

SPRINKLER LOCATIONS ARE TO SCALE
 PIPE LOCATIONS ARE DIAGRAMMATIC
 ALL SPRINKLERS TO BE INSTALLED ON

IRRIGATION NOTES


- 32mm SCH 80
- MAINLINE DEPTH TO BE NO LESS THAN 460mm
 LATERAL DEPTH TO BE NO LESS THAN 410mm
 ELECTRIC CONTROL VALVES TO BE COVERED WITH 12" 4. ALL COMPONENTS TO BE INSTALLED AS PER MANUFACTURERS RECOMMENDATIONS

VALVE BOX

- 8. LOCATE VALVES/OCVS OUT OF HIGH TRAFFIC AREAS 9. WIRE SPLICE CONNECTIONS TO BE WATERPROOF 10. QCV TO BE LOCATED IN 10" VALVE BOX 11. ALL SLEEVES TO BE 2X PIPE RUN THROUGH THEM
- 12 INSTALL ALL COMPONENTS AS PER LOCAL, STATE, FEDERAL CODES
- 13. REFER TO HUNTER INSTALLATION DETAILS
 14. REFER TO HUNTER CATALOG FOR PERFORMANCE SPECIFICATIONS
- 16. ADD HUNTER "AS" FOR PRESSURE REGULATED VALVE 15. ADD HUNTER "FS" FOR DIRTY WATER VALVE

SYSTEM PERFORMANCE DATA

A9	A8	A7	A6	A5	Α4	A3	Æ	A		ZONE
1.5	<u></u>	-1 -51		SIZE						
10.1	10.1	10.1	10.1	8.3	16.5	16.5	8.3	16.5	m³/hr	FLC
169	169	169	169	138	275	275	138	275	/mln	×
14.1	14.1	14.1	14.1	46.1	21.1	21.1	46.1	21.1	mm/hr	R
.86	86	86	83	83	83	83	83	83		2
1.1	1.1	1.1	1.2	1.2	1.2	1.2	1.2	1.2		SC (10% MHDOW)



SHEET

유

Hunter Industries 1940 Dlamond Street San Marcos, California 92078 SpecPro Technical Assistance 1-800-319-4796 www.HunterIndustries.com

SOCCER FIELD 60 x 90M

I-40 FOUR ROW DESIGN

