

VALVE ID GUIDE

50"hr PRECIPITATION RATE

GPM VALVE SIZE STATION NUMBER

## IRRIGATION NOTES

IRRIGATION LEGEND

PRODUCT DESCRIPTION

- 4. ALL COMPONENTS TO BE INSTALLED AS PER MANUFACTURERS SPRINKLER LOCATIONS ARE TO SCALE
   PIPE LOCATIONS ARE DIAGRAMMATIC
   ALL SPRINKLERS TO BE INSTALLED ON 1" SCH 80 SWING
   JOINTS
- 5. MAINLINE DEPTH TO BE NO LESS THAN 18"
  6. LATERAL DEPTH TO BE NO LESS THAN 16"
  7. ELECTRIC CONTROL VALVES TO BE COVERED WITH 12" VALVE RECOMMENDATIONS

8

ISOLATION VALVE LINE SIZED

● HUNTER I-25-36S-XXI-25-6P-36S-XX NOZZLE AS SHOWN

● HUNTER I-25-ADS-XXI-25-6P-ADS-XX NOZZLE AS SHOWN

NOZZLE PERFORMANCE:

#15 @ 70 PSI- 15.2 GPM, 57 63 'RADIUS

● HUNTER ICVIBEV ELECTRIC CONTROL VALVE SIZE AS SHOWN

• HUNTER HQ-44-XX-AW QUIDK COUPLER VALVE (OPTIONAL)

• HUNTER HC-44-XX-AW QUID STATE METAL CABINET CONTROLLER

© HUNTER SOLAR-SYNC-SEN ON SITE WEATHER SENSOR

© HUNTER SOLAR-SYNC-SEN ON SITE WEATHER SENSOR

© HUNTER SOLAR-SYNC-SEN ON SITE WEATHER SENSOR

© MATER METER MINIMUM SIZE @ 61 GPM IS 2.0"

© BOCKFLOW PREVENTER SIZED TO SYSTEM GPM


— MAINLINE PIPE

LATERAL PIPE

LATERAL PIPE

- 8. LOCATE VALVES/QCV'S OUT OF HIGH TRAFFIC AREAS
  9. WIRE SPLICE CONNECTIONS TO BE WATERPROOF
  10. QCV TO BE LOCATED IN 10" VALVE BOX
  11. ALL SLEEVES TO BE 2X PIPE RUN THROUGH THEM
  12. INSTALL ALL COMPONENTS AS PER LOCAL, STATE,
- 13. REFER TO HUNTER INSTALLATION DETAILS
  14. REFER TO HUNTER CATALOG FOR PERFORMANCE FEDERAL CODES
- SPECIFICATIONS
- 15. ADD HUNTER "FS" FOR DIRTY WATER VALVE
  16. ADD HUNTER "AS" FOR PRESSURE REGULATED VALVE

## SYSTEM PERFORMANCE DATA



Hunter industries offers this plan as a general guide for estimating purposes and offers on indemnity, expressed or implied, for projects installed from this plan. Because of the many variables of every system and of every site we recommend that a qualified infigation designer be consulted.

SHEET OF 1

Hunter Industries 1940 Diamond Street San Marcos, Callfornia 92078 SpecPro Technical Assistance 1-800-319-4796 www.HunterIndustries.com

OFFICIAL SOCCER FIELD 300 x 200

I-25 FIVE ROW DESIGN



WATER REQUIREMENT

-AT FIELD ELEVATION
--WITHIN 100' OF FIELD
--DOWNSTREAM OF BACKFLOW IS 61
GPM @ 85 PSI