



DETAIL LEGEND:

- ① IRRIGATION CONTROLLER, INDOOR/OUTDOOR WALL MOUNT, PER PLAN
- ② FLOW-CLIK MODULE AND PROVIDED CABLE
- ③ PLASTIC CONTROLLER DOOR
- ④ CONTROL WIRE CONDUIT TO PLANTER, SIZE AS REQUIRED
- ⑤ 120 VAC CABLE FOR CONNECTION TO GROUNDED 120 VAC POWER SOURCE (230 VAC FOR INTERNATIONAL MODELS)
- ⑥ TWO (2) WIRES TO SENSOR TERMINALS IN CONTROLLER - WHITE
- ⑦ TWO (2) WIRES TO 24 VAC TERMINALS IN CONTROLLER - YELLOW
- ⑧ TWO (2) WIRES TO FLOW-CLIK SENSOR - BLACK, RED
- ⑨ SURFACE TO MOUNT CONTROLLER PER PLAN

NOTES:

- A. COMPLETE INSTALLATION IN ACCORDANCE WITH HUNTER'S SPECIFICATIONS. REFER TO PRODUCT INSTALLATION GUIDE PRIOR TO INSTALLATION.
- B. CONTROLLER ACCEPTS 120 VOLTS A.C. OR 230 VOLTS A.C. (INTERNATIONAL MODEL). HARD WIRE OR PLUG INTO A GROUNDED POWER SOURCE.
- C. MODEL NUMBER AND SPECIFICATIONS PER PLAN.
- D. MOUNT CONTROLLER LCD SCREEN AT EYE LEVEL WHEN FEASIBLE.



IRRIGATION CONTROLLER, WALL MOUNT WITH FLOW-CLIK

Hunter® S-FC.1

NOT TO SCALE
REV: 2019-09-09