Hunter® Built on Innovation®

Pro [illegible]

[illegible]

[illegible]

- [illegible]
- [illegible] 40 [illegible]/[illegible] 2.4 [illegible] 5.2 [illegible]
- [illegible] 0° [illegible] 360° [illegible]
- [illegible]
- [illegible]
- 0° [illegible]
- [illegible]
- [illegible]
- [illegible]2.1 bar (210 kPa)
- [illegible] Pro-Spray PRS30 [illegible] 2.1 bar (210 kPa)
- [illegible]2 [illegible]

8A-HE [illegible]

2.4 [illegible]

[illegible] 0° [illegible] 360°

[illegible] 20°

[illegible]	[illegible]		[illegible]	[illegible]		[illegible] mm/h	
	bar	kPa	m	[illegible]/[illegible]	[illegible]/[illegible]	■	▲
90°	1.0	100	2.0	0.05	0.87	52	60
	1.5	150	2.2	0.06	1.02	51	59
	2.1	**210**	**2.4**	**0.06**	**1.06**	**44**	**51**
	2.5	250	2.6	0.07	1.21	43	50
	3.0	300	2.8	0.08	1.32	41	47
180°	1.0	100	2.0	0.10	1.65	49	57
	1.5	150	2.2	0.11	1.85	46	53
	2.1	**210**	**2.4**	**0.12**	**2.08**	**43**	**50**
	2.5	250	2.6	0.14	2.37	42	48
	3.0	300	2.8	0.15	2.57	39	45
270°	1.0	100	2.0	0.15	2.47	49	57
	1.5	150	2.2	0.17	2.78	46	53
	2.1	**210**	**2.4**	**0.19**	**3.11**	**43**	**50**
	2.5	250	2.6	0.21	3.55	42	48
	3.0	300	2.8	0,23	3.86	39	45
360°	1.0	100	2.0	0.20	3.29	49	57
	1.5	150	2.2	0.22	3.71	46	53
	2.1	**210**	**2.4**	**0.25**	**4.15**	**43**	**50**
	2.5	250	2.6	0.28	4.73	42	50
	3.0	300	2.8	0.31	5.50	39	45

10A-HE

3.0

0° 360°

25°

						mm/h	
	bar	kPa	m	//			
90°	1.0	100	2.7	0.08	1.36	45	52
	1.5	150	2.8	0.09	1.55	48	55
	2.1	**210**	**3.0**	**0.10**	**1.67**	**44**	**51**
	2.5	250	3.1	0.11	1.82	45	52
	3.0	300	3.2	0.12	1.93	45	52
180°	1.0	100	2.7	0.16	2.65	44	50
	1.5	150	2.8	0.18	2.94	45	52
	2.1	**210**	**3.0**	**0.19**	**3.24**	**43**	**50**
	2.5	250	3.1	0.21	3.52	44	51
	3.0	300	3.2	0,23	3.79	44	51
270°	1.0	100	2.7	0.24	3.97	44	50
	1.5	150	2.8	0.26	4.41	45	52
	2.1	**210**	**3.0**	**0.29**	**4.85**	**43**	**50**
	2.5	250	3.1	0.32	5.28	44	51
	3.0	300	3.2	0.34	5.68	44	51
360°	1.0	100	2.7	0.32	5.30	44	50
	1.5	150	2.8	0.35	5.88	45	52
	2.1	**210**	**3.0**	**0.39**	**6.47**	**43**	**50**
	2.5	250	3.1	0.42	7.04	44	51
	3.0	300	3.2	0.45	7.57	44	51

12A-HE

3.7

0° 360°

25°

□□	□□		□□	□□		□□□□ mm/h	
	bar	kPa	m	□□□/□□ □/□		■	▲
90°	1.0	100	3.3	0.12	2.01	44	51
	1.5	150	3.5	0.13	2.23	44	51
	2.1	**210**	**3.7**	**0.14**	**2.38**	**42**	**48**
	2.5	250	3.8	0.16	2.65	44	51
	3.0	300	3.9	0.17	2.84	45	51
180°	1.0	100	3.3	0,23	3.88	43	49
	1.5	150	3.5	0.125	4.24	42	48
	2.1	**210**	**3.7**	**0.28**	**4.62**	**40**	**47**
	2.5	250	3.8	0.30	5.03	42	48
	3.0	300	3.9	0.33	5.53	42	50
270°	1.0	100	3.3	0.35	5.82	43	49
	1.5	150	3.5	0.38	6.36	42	48
	2.1	**210**	**3.7**	**0.42**	**6.93**	**40**	**47**
	2.5	250	3.8	0.45	7.55	42	48
	3.0	300	3.9	0.50	8.29	44	50
360°	1.0	100	3.3	0.47	7.76	43	49
	1.5	150	3.5	0.51	8.48	42	48
	2.1	**210**	**3.7**	**0.55**	**9.24**	**40**	**47**
	2.5	250	3.8	0.60	10.07	42	48
	3.0	300	3.9	0.66	11.05	44	50

15A-HE ■□

4.6 □

□□□□□ 0° □ 360°

□□□□ 25°

□□	□□		□□	□□		□□□□ mm/h	
	bar	kPa	m	□□□/□□ □/□		■	▲
90°	1.0	100	4.2	0.18	2.95	40	46
	1.5	150	4.4	0.20	3.33	41	48
	2.1	**210**	**4.6**	**0.22**	**3.63**	**41**	**48**
	2.5	250	4.7	0.24	4.05	44	51
	3.0	300	4.8	0.26	4.28	45	51
180°	1.0	100	4.2	0.35	5.78	39	45
	1.5	150	4.4	0.38	6.38	40	46
	2.1	**210**	**4.6**	**0.42**	**7.08**	**40**	**46**
	2.5	250	4.7	0.47	7.76	42	49
	3.0	300	4.8	0.50	8.39	44	50
270°	1.0	100	4.2	0.52	8.67	39	45
	1.5	150	4.4	0.57	9.58	40	46
	2.1	**210**	**4.6**	**0.64**	**10.62**	**40**	**46**
	2.5	250	4.7	0.70	11.64	42	49
	3.0	300	4.8	0.75	12.59	42	50
360°	1.0	100	4.2	0.69	11.56	39	45
	1.5	150	4.4	0.77	12.77	40	46
	2.1	**210**	**4.6**	**0.85**	**14.16**	**40**	**46**
	2.5	250	4.7	0.93	15.52	42	49
	3.0	300	4.8	1.01	16.78	44	50

17A-HE

4.6

0° 360°

25°

						mm/h	
	bar	kPa	m				
90°	1.0	100	4.6	0.22	3.61	41	47
	1.5	150	4.8	0.24	4.04	42	49
	2.1	**210**	**5.2**	**0.28**	**4.69**	**42**	**48**
	2.5	250	5.3	0.29	4.90	42	48
	3.0	300	5.4	0.31	5.25	43	50
180°	1.0	100	4.6	0.40	6.68	38	44
	1.5	150	4.8	0.46	7.70	40	46
	2.1	**210**	**5.2**	**0.54**	**8.93**	**40**	**46**
	2.5	250	5.3	0.56	9.33	40	46
	3.0	300	5.4	0.50	10.02	41	48
270°	1.0	100	4.6	0.60	10.02	38	44
	1.5	150	4.8	0.69	11.55	40	46
	2.1	**210**	**5.2**	**0.80**	**13.40**	**40**	**46**
	2.5	250	5.3	0.84	14.00	40	46
	3.0	300	5.4	0.90	15.05	41	48
360°	1.0	100	4.6	0.80	13.36	38	44
	1.5	150	4.8	0.92	15.40	40	46
	2.1	**210**	**5.2**	**1.07**	**17.87**	**40**	**46**
	2.5	250	5.3	1.12	18.66	40	46
	3.0	300	5.4	1.29	20.06	41	48

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

https://www.hunterirrigation.com/cn/irrigation-product/pro-gaoxiaopenzui
090726