PRU-LV

Product Line: Pressure Regulators
Product Model: Senninger® Pressure Regulators
Part Number: See additional information
Description: Pressure Regulating Ultra Limit Valve
Warranty: 1 year on materials, workmanship, and performance

Dimensions

Inlet Sizes: 2" female NPT, 2" female BSPT

Operating Specifications

Flows: up to 22713 L/hr
Pressures: 0.69 - 4.14 bar
Oulet Sizes: 2" female NPT, 2" female BSPT

Shipping Information

Additional Information

PRU-LV Models

Part Number	Description
NPT models	
PRULV108F8F	10 psi, inlet 2" F NPT, outlet 2" F NPT
PRULV158F8F	15 psi, inlet 2" F NPT, outlet 2" F NPT
PRULV208F8F	20 psi, inlet 2" F NPT, outlet 2" F NPT
PRULV258F8F	25 psi, inlet 2" F NPT, outlet 2" F NPT
PRULV308F8F	30 psi, inlet 2" F NPT, outlet 2" F NPT
PRULV408F8F	40 psi, inlet 2" F NPT, outlet 2" F NPT
PRULV508F8F	50 psi, inlet 2" F NPT, outlet 2" F NPT
PRULV608F8F	60 psi, inlet 2" F NPT, outlet 2" F NPT
BSPT models	
PRULV108FB8FB	10 psi, inlet 2" F BSPT, outlet 2" F BSPT
PRULV158FB8FB	15 psi, inlet 2" F BSPT, outlet 2" F BSPT
PRULV208FB8FB	20 psi, inlet 2" F BSPT, outlet 2" F BSPT
PRULV258FB8FB	25 psi, inlet 2" F BSPT, outlet 2" F BSPT
PRULV308FB8FB	30 psi, inlet 2" F BSPT, outlet 2" F BSPT
PRULV408FB8FB	40 psi, inlet 2" F BSPT, outlet 2" F BSPT
PRULV508FB8FB	50 psi, inlet 2" F BSPT, outlet 2" F BSPT
PRULV608FB8FB	60 psi, inlet 2" F BSPT, outlet 2" F BSPT

	Model	Market	Preset Outlet Pressure	Maximum Inlet Pressure*	Flow Range	Inlet Sizes	Outlet Sizes
	MPR	Solid Set/ Nursery	1.0 - 2.8 bar	5.5 bar	114 - 804 L/hr	1/2" M NPT	1/2" F NPT
	PRLG	Solid Set/ Nursery	0.69 - 2.76 bar	8.27 bar	114 - 1590 L/hr	3/4" F hose, 3/4" F NPT, tape lock barb (5/8"), 500 lock barb (16 mm), 600 lock barb (18 mm)	3/4" M hose, 3/4" M NPT, tape lock barb (5/8"), 500 lock barb (16 mm), 600 lock barb (18 mm)
	PRMP	Solution Mining	0.69 - 2.76 bar		114 - 1590 L/hr	3/4" F hose, 3/4" F NPT, tape (5/8"), 500 (16 mm), 600 (18 mm)	3/4" F hose, 3/4" F NPT, tape (5/8"), 500 (16 mm), 600 (18 mm)
	PRL	Pivot Solid Set/ Nursery Solution Mining	0.41 - 2.76 bar	8.27 bar	114 - 1817 L/hr	3/4" F NPT, 3/4" F hose	3/4" F NPT
	PSR-2	Pivot Solid Set/ Nursery	0.41 - 3.45 bar	8.96 bar	114 - 3407 L/hr	3/4" F NPT	3/4" F NPT
	Filter Regulator	Pivot Solid Set/ Nursery	0.41 - 3.45 bar	8.96 bar	114 - 3407 L/hr	3/4" M NPT	3/4" F NPT
	PMR-MF	Pivot	0.41 - 4.14 bar	9.65 bar	454 - 4543 L/hr	3/4" F NPT, 1" F NPT, 1" F BSPT	3/4" F NPT, 1" F NPT, 1" F BSPT

Solid Set/ Nursery

Solution Mining

	PR-HF	Solid Set/ Nursery	0.69 - 3.45 bar	8.96 bar	2271 - 7268 L/hr	1-1/4" F NPT, 1-1/4" F BSPT	1" F NPT, 1-1/4" F NPT, 1" F BSPT, 1-1/4" F BSPT
	PRU	Solid Set/ Nursery	0.41 - 4.14 bar	9.65 bar	4543 - 22713 L/hr	2" F NPT, 2" F BSPT	2" F NPT, 2" F BSPT
	PRLV	Solid Set/ Nursery	0.69 - 4.14 bar	8.62 bar	up to 4088 L/hr	3/4" F NPT, 1" F NPT	3/4" F NPT, 1" F NPT
	PRU-LV	Solid Set/ Nursery	0.69 - 4.14 bar	8.62 bar	Max: 22713 L/hr	2" F NPT, 2" F BSPT	2" F NPT, 2" F BSPT

* Varies by model, check models chart.

MPR MODELS	Preset Outlet Pressure	Maximum Inlet Pressure	Flow Range	Inlet Sizes	Outlet Sizes
MPR152M2F	1.0 bar	3.1 bar	114 - 513 L/hr	1/2" M NPT	1/2" F NPT
MPR202M2F	1.4 bar	3.5 bar	114 - 559 L/hr	1/2" M NPT	1/2" F NPT
MPR302M2F	2.1 bar	4.1 bar	136 - 704 L/hr	1/2" M NPT	1/2" F NPT
MPR402M2F	2.8 bar	5.5 bar	159 - 804 L/hr	1/2" M NPT	1/2" F NPT

The pressure regulator shall maintain the predetermined operating pressure provided that the inlet pressure is at least 5 psi (0.3 bar) above the expected outlet pressure, but not exceeding the maximum inlet pressure as shown above.

Recommended for outdoor use only. Not NSF certified.

PRLG DESIGN CRITERIA	Preset Outlet Pressure	Maximum Inlet Pressure	Flow Range	Inlet Sizes	Outlet Sizes
PRLG10TLBTLB	0.69 bar	1.72 bar	114 - 1590 L/hr	tape barb (5/8") with lock nuts (green)	tape barb (5/8") with lock nuts (green)
PRLG15TLBTLB	1.03 bar	1.72 bar	114 - 1590 L/hr	tape barb (5/8") with lock nuts (green)	tape barb (5/8") with lock nuts (green)
PRLG105LB5LB	0.69 bar	3.45 bar	114 - 1590 L/hr	500 barb (16 mm) with lock nuts (black)	500 barb (16 mm) with lock nuts (black)
PRLG155LB5LB	1.03 bar	3.45 bar	114 - 1590 L/hr	500 barb (16 mm) with lock nuts (black)	500 barb (16 mm) with lock nuts (black)
PRLG205LB5LB	1.38 bar	3.45 bar	114 - 1590 L/hr	500 barb (16 mm) with lock nuts (black)	500 barb (16 mm) with lock nuts (black)
PRLG106LB6LB	0.69 bar	3.45 bar	114 - 1590 L/hr	600 barb (18 mm) with lock nuts (black)	600 barb (18 mm) with lock nuts (black)
PRLG156LB6LB	1.03 bar	3.45 bar	114 - 1590 L/hr	600 barb (18 mm) with lock nuts (black)	600 barb (18 mm) with lock nuts (black)
PRLG206LB6LB	1.38 bar	3.45 bar	114 - 1590 L/hr	600 barb (18 mm) with lock nuts (black)	600 barb (18 mm) with lock nuts (black)
PRLG103FH3MH	0.69 bar	6.20 bar	114 - 1590 L/hr	¾" F hose	¾" M hose
PRLG153FH3MH	1.03 bar	6.55 bar	114 - 1590 L/hr	¾" F hose	¾" M hose
PRLG203FH3MH	1.38 bar	6.89 bar	114 - 1590 L/hr	¾" F hose	¾" M hose
PRLG253FH3MH	1.72 bar	7.24 bar	114 - 1590 L/hr	¾" F hose	¾" M hose
PRLG303FH3MH	2.07 bar	7.58 bar	114 - 1590 L/hr	¾" F hose	¾" M hose
PRLG353FH3MH	2.41 bar	7.93 bar	114 - 1590 L/hr	¾" F hose	¾" M hose
PRLG403FH3MH	2.76 bar	8.27 bar	114 - 1590 L/hr	¾" F hose	¾" M hose
PRLG103F3M	0.69 bar	6.20 bar	114 - 1590 L/hr	¾" F NPT	¾" M NPT
PRLG153F3M	1.03 bar	6.55 bar	114 - 1590 L/hr	¾" F NPT	¾" M NPT
PRLG203F3M	1.38 bar	6.89 bar	114 - 1590 L/hr	¾" F NPT	¾" M NPT
PRLG253F3M	1.72 bar	7.24 bar	114 - 1590 L/hr	¾" F NPT	¾" M NPT
PRLG303F3M	2.07 bar	7.58 bar	114 - 1590 L/hr	¾" F NPT	¾" M NPT
PRLG353F3M	2.41 bar	7.93 bar	114 - 1590 L/hr	¾" F NPT	¾" M NPT
PRLG403F3M	2.76 bar	8.27 bar	114 - 1590 L/hr	¾" F NPT	¾" M NPT

The pressure regulator shall maintain the predetermined operating pressure provided that the inlet pressure is at least 0.34 bar above the expected outlet pressure, but not exceeding the maximum inlet pressure as shown above.

Recommended for outdoor use only. Not NSF certified.

PRMP DESIGN CRITERIA	Preset Operating Pressure	Maximum Inlet Pressure	Flow Range	Inlet Sizes	Outlet Sizes
PRMP103FH3MH	0.69 bar	6.20 bar	114 - 1590 L/hr	3/4" F hose	3/4" M hose
PRMP153FH3MH	1.03 bar	6.55 bar	114 - 1590 L/hr	3/4" F hose	3/4" M hose
PRMP203FH3MH	1.38 bar	6.89 bar	114 - 1590 L/hr	3/4" F hose	3/4" M hose
PRMP253FH3MH	1.72 bar	7.24 bar	114 - 1590 L/hr	3/4" F hose	3/4" M hose
PRMP303FH3MH	2.07 bar	7.58 bar	114 - 1590 L/hr	3/4" F hose	3/4" M hose
PRMP353FH3MH	2.41 bar	7.93 bar	114 - 1590 L/hr	3/4" F hose	3/4" M hose
PRMP403FH3MH	2.76 bar	8.27 bar	114 - 1590 L/hr	3/4" F hose	3/4" M hose
PRMP103F3M	0.69 bar	6.20 bar	114 - 1590 L/hr	3/4" F NPT	3/4" M NPT
PRMP153F3M	1.03 bar	6.55 bar	114 - 1590 L/hr	3/4" F NPT	3/4" M NPT
PRMP203F3M	1.38 bar	6.89 bar	114 - 1590 L/hr	3/4" F NPT	3/4" M NPT
PRMP253F3M	1.72 bar	7.24 bar	114 - 1590 L/hr	3/4" F NPT	3/4" M NPT
PRMP303F3M	2.07 bar	7.58 bar	114 - 1590 L/hr	3/4" F NPT	3/4" M NPT
PRMP353F3M	2.41 bar	7.93 bar	114 - 1590 L/hr	3/4" F NPT	3/4" M NPT
PRMP403F3M	2.76 bar	8.27 bar	114 - 1590 L/hr	3/4" F NPT	3/4" M NPT
PRMP10TLBTLB	0.69 bar	1.72 bar	114 - 1590 L/hr	tape (5/8")	tape (5/8")
PRMP15TLBTLB	1.03 bar	1.72 bar	114 - 1590 L/hr	tape (5/8")	tape (5/8")
PRMP105LB5LB	0.69 bar	3.45 bar	114 - 1590 L/hr	500 (16 mm)	500 (16 mm)
PRMP155LB5LB	1.03 bar	3.45 bar	114 - 1590 L/hr	500 (16 mm)	500 (16 mm)
PRMP205LB5LB	1.38 bar	3.45 bar	114 - 1590 L/hr	500 (16 mm)	500 (16 mm)
PRMP106LB6LB	0.69 bar	3.45 bar	114 - 1590 L/hr	600 (18 mm)	600 (18 mm)
PRMP156LB6LB	1.03 bar	3.45 bar	114 - 1590 L/hr	600 (18 mm)	600 (18 mm)
PRMP2056LB6LB	1.38 bar	3.45 bar	114 - 1590 L/hr	600 (18 mm)	600 (18 mm)

The pressure regulator shall maintain the predetermined operating pressure provided that the inlet pressure is at least 0.34 bar above the expected outlet pressure, but not exceeding the maximum inlet pressure as shown above.

PRL MODELS	Preset Outlet Pressure	Maximum Inlet Pressure	Flow Range	Inlet Sizes	Outlet Sizes
PRL06	0.41 bar	5.51 bar	114 - 1136 L/hr	3/4" F NPT, 3/4" F hose	3/4" F NPT
PRL10	0.69 bar	6.20 bar	114 - 1817 L/hr	3/4" F NPT, 3/4" F hose	3/4" F NPT
PRL12	0.83 bar	6.20 bar	114 - 1817 L/hr	3/4" F NPT, 3/4" F hose	3/4" F NPT
PRL15	1.03 bar	6.55 bar	114 - 1817 L/hr	3/4" F NPT, 3/4" F hose	3/4" F NPT
PRL20	1.38 bar	6.89 bar	114 - 1817 L/hr	3/4" F NPT, 3/4" F hose	3/4" F NPT
PRL25	1.72 bar	7.24 bar	114 - 1817 L/hr	3/4" F NPT, 3/4" F hose	3/4" F NPT
PRL30	2.07 bar	7.58 bar	114 - 1817 L/hr	3/4" F NPT, 3/4" F hose	3/4" F NPT
PRL35	2.41 bar	7.93 bar	114 - 1817 L/hr	3/4" F NPT, 3/4" F hose	3/4" F NPT
PRL40	2.76 bar	8.27 bar	114 - 1817 L/hr	3/4" F NPT, 3/4" F hose	3/4" F NPT

The pressure regulator shall maintain the predetermined operating pressure provided that the inlet pressure is at least 5 psi (0.34 bar) above the expected outlet pressure, but not exceeding the maximum inlet pressure as shown above.

Recommended for outdoor use only. Not NSF certified.

PSR2 MODELS	Preset Outlet Pressure	Maximum Inlet Pressure	Flow Range	Inlet Sizes	Outlet Sizes
PSR2 06	0.41 bar	5.51 bar	114 - 3407 L/hr	3/4" F NPT	3/4" F NPT
PSR2 10	0.69 bar	6.20 bar	114 - 3407 L/hr	3/4" F NPT	3/4" F NPT
PSR2 12	0.83 bar	6.20 bar	114 - 3407 L/hr	3/4" F NPT	3/4" F NPT
PSR2 15	1.03 bar	6.55 bar	114 - 3407 L/hr	3/4" F NPT	3/4" F NPT
PSR2 20	1.38 bar	6.89 bar	114 - 3407 L/hr	3/4" F NPT	3/4" F NPT
PSR2 25	1.72 bar	7.24 bar	114 - 3407 L/hr	3/4" F NPT	3/4" F NPT
PSR2 30	2.07 bar	7.58 bar	114 - 3407 L/hr	3/4" F NPT	3/4" F NPT
PSR2 35	2.41 bar	7.93 bar	114 - 3407 L/hr	3/4" F NPT	3/4" F NPT
PSR2 40	2.76 bar	8.27 bar	114 - 3407 L/hr	3/4" F NPT	3/4" F NPT
PSR2 50	3.45 bar	8.96 bar	114 - 3407 L/hr	3/4" F NPT	3/4" F NPT

The pressure regulator shall maintain the predetermined operating pressure provided that the inlet pressure is at least 5 psi (0.34 bar) above the expected outlet pressure, but not exceeding the maximum inlet pressure as shown above.

Recommended for outdoor use only. Not NSF certified.

FILTER REGULATOR MODELS	Preset Outlet Pressure	Maximum Inlet Pressure	Mesh Filter Screen	Mesh Orifice (microns)	UP3 Nozzle Number
FPSR2063M3F20			20 mesh (black rings)	841	#13 - #26
FPSR2063M3F30	0.41 bar	5.51 bar	30 mesh (green rings)	595	#6 - #12.5
FPSR2063M3F40			40 mesh (grey rings)	400	#2 - #5.5
FPSR2103M3F20			20 mesh (black rings)	841	#13 - #26
FPSR2103M3F30	0.69 bar	6.20 bar	30 mesh (green rings)	595	#6 - #12.5
FPSR2103M3F40			40 mesh (grey rings)	400	#2 - #5.5
FPSR2153M3F20			20 mesh (black rings)	841	#13 - #26
FPSR2153M3F30	1.03 bar	6.55 bar	30 mesh (green rings)	595	#6 - #12.5
FPSR2153M3F40			40 mesh (grey rings)	400	#2 - #5.5
FPSR2203M3F20			20 mesh (black rings)	841	#13 - #26
FPSR2203M3F30	1.38 bar	6.89 bar	30 mesh (green rings)	595	#6 - #12.5
FPSR2203M3F40			40 mesh (grey rings)	400	#2 - #5.5
FPSR2103M3F120	0.69 bar	6.20 bar	120 mesh screen (red rings)	125	1140 - 3407 L/hr
FPSR2103M3F140			140 mesh screen (blue rings)	105	
FPSR2153M3F120	1.03 bar	6.55 bar	120 mesh screen (red rings)	125	1140 - 3407 L/hr
FPSR2153M3F140			140 mesh screen (blue rings)	105	
FPSR2203M3F120	1.38 bar	6.89 bar	120 mesh screen (red rings)	125	1140 - 3407 L/hr
FPSR2203M3F140			140 mesh screen (blue rings)	105	

Shaded models designed for use with drip systems.

The pressure regulator shall maintain the predetermined operating pressure provided that the inlet pressure is at least 5 psi (0.34 bar) above the expected outlet pressure, with flows up to 11 gpm (2498 L/hr), but not exceeding the maximum inlet pressure of 80 psi (5.5 bar) above the model's pressure rating. Higher flows require additional inlet pressure to engage the regulator. Where flows are greater than 11 gpm (2498 L/hr), the inlet pressure should be at least 9 psi (0.62 bar) above the expected outlet pressure but not exceeding the maximum inlet pressure as shown above.

Pressure regulators should always be installed downstream of all shut-off valves.

Recommended for outdoor use only. Not NSF certified.

PR-HF MODELS	Preset Outlet Pressure	Maximum Inlet Pressure	Flow Range	Inlet Sizes	Outlet Sizes
PR10HF	0.69 bar	6.20 bar	2271 - 7268 L/hr	1¼" F NPT, 1¼" F BSPT	1" F NPT, 1¼" F NPT, 1" F BSPT, 1¼" F BSPT
PR15HF	1.03 bar	6.55 bar	2271 - 7268 L/hr	1¼" F NPT, 1¼" F BSPT	1" F NPT, 1¼" F NPT, 1" F BSPT, 1¼" F BSPT
PR20HF	1.38 bar	6.89 bar	2271 - 7268 L/hr	1¼" F NPT, 1¼" F BSPT	1" F NPT, 1¼" F NPT, 1" F BSPT, 1¼" F BSPT
PR25HF	1.72 bar	7.24 bar	2271 - 7268 L/hr	1¼" F NPT, 1¼" F BSPT	1" F NPT, 1¼" F NPT, 1" F BSPT, 1¼" F BSPT
PR30HF	2.07 bar	7.58 bar	2271 - 7268 L/hr	1¼" F NPT, 1¼" F BSPT	1" F NPT, 1¼" F NPT, 1" F BSPT, 1¼" F BSPT
PR40HF	2.76 bar	8.27 bar	2271 - 7268 L/hr	1¼" F NPT, 1¼" F BSPT	1" F NPT, 1¼" F NPT, 1" F BSPT, 1¼" F BSPT
PR50HF	3.45 bar	8.96 bar	2271 - 7268 L/hr	1¼" F NPT, 1¼" F BSPT	1" F NPT, 1¼" F NPT, 1" F BSPT, 1¼" F BSPT

The pressure regulator shall maintain the predetermined operating pressure provided that the inlet pressure is at least 5 psi (0.34 bar) above the expected outlet pressure, but not exceeding the maximum inlet pressure as shown above.

Recommended for outdoor use only. Not NSF certified.

PMR-MF MODELS	Preset Outlet Pressure	Maximum Inlet Pressure	Flow Range	Inlet Sizes	Outlet Sizes
PMR06MF	0.41 bar	5.51 bar	909 - 3634 L/hr	3/4" F NPT, 1" F NPT, 1" F BSPT	3/4" F NPT, 1" F NPT, 1" F BSPT
PMR10MF	0.69 bar	6.20 bar	909 - 3634 L/hr	3/4" F NPT, 1" F NPT, 1" F BSPT	3/4" F NPT, 1" F NPT, 1" F BSPT
PMR12MF	0.83 bar	6.20 bar	454 - 4543 L/hr	3/4" F NPT, 1" F NPT, 1" F BSPT	3/4" F NPT, 1" F NPT, 1" F BSPT
PMR15MF	1.03 bar	6.55 bar	454 - 4543 L/hr	3/4" F NPT, 1" F NPT, 1" F BSPT	3/4" F NPT, 1" F NPT, 1" F BSPT
PMR20MF	1.38 bar	6.89 bar	454 - 4543 L/hr	3/4" F NPT, 1" F NPT, 1" F BSPT	3/4" F NPT, 1" F NPT, 1" F BSPT
PMR25MF	1.72 bar	7.24 bar	454 - 4543 L/hr	3/4" F NPT, 1" F NPT, 1" F BSPT	3/4" F NPT, 1" F NPT, 1" F BSPT
PMR30MF	2.07 bar	7.58 bar	454 - 4543 L/hr	3/4" F NPT, 1" F NPT, 1" F BSPT	3/4" F NPT, 1" F NPT, 1" F BSPT
PMR35MF	2.41 bar	7.93 bar	454 - 4543 L/hr	3/4" F NPT, 1" F NPT, 1" F BSPT	3/4" F NPT, 1" F NPT, 1" F BSPT
PMR40MF	2.76 bar	8.27 bar	454 - 4543 L/hr	3/4" F NPT, 1" F NPT, 1" F BSPT	3/4" F NPT, 1" F NPT, 1" F BSPT
PMR50MF	3.45 bar	8.96 bar	454 - 4543 L/hr	3/4" F NPT, 1" F NPT, 1" F BSPT	3/4" F NPT, 1" F NPT, 1" F BSPT
PMR60MF	4.14 bar	9.65 bar	454 - 4543 L/hr	3/4" F NPT, 1" F NPT, 1" F BSPT	3/4" F NPT, 1" F NPT, 1" F BSPT

The pressure regulator shall maintain the predetermined operating pressure provided that the inlet pressure is at least 5 psi (0.34 bar) above the expected outlet pressure, but not exceeding the maximum inlet pressure as shown above.

Recommended for outdoor use only. Not NSF certified.

PRU MODELS	Preset Outlet Pressure	Maximum Inlet Pressure	Flow Range	Inlet Sizes	Outlet Sizes
PRU10	0.69 bar	6.20 bar	4543 - 22713 L/hr	2" F NPT, 2" F BSPT	2" F NPT, 2" F BSPT
PRU15	1.03 bar	6.55 bar	4543 - 22713 L/hr	2" F NPT, 2" F BSPT	2" F NPT, 2" F BSPT
PRU20	1.38 bar	6.89 bar	4543 - 22713 L/hr	2" F NPT, 2" F BSPT	2" F NPT, 2" F BSPT
PRU25	1.72 bar	7.24 bar	4543 - 22713 L/hr	2" F NPT, 2" F BSPT	2" F NPT, 2" F BSPT
PRU30	2.07 bar	7.58 bar	4543 - 22713 L/hr	2" F NPT, 2" F BSPT	2" F NPT, 2" F BSPT
PRU40	2.76 bar	8.27 bar	4543 - 22713 L/hr	2" F NPT, 2" F BSPT	2" F NPT, 2" F BSPT
PRU50	3.45 bar	8.96 bar	4543 - 22713 L/hr	2" F NPT, 2" F BSPT	2" F NPT, 2" F BSPT
PRU60	4.14 bar	9.65 bar	4543 - 22713 L/hr	2" F NPT, 2" F BSPT	2" F NPT, 2" F BSPT

The pressure regulator shall maintain the predetermined operating pressure provided that the inlet pressure is at least 5 psi (0.34 bar) above the expected outlet pressure, but not exceeding the maximum inlet pressure as shown above.

Recommended for outdoor use only. Not NSF certified.

PRU-LV MODELS	Preset Outlet Pressure	Maximum Inlet Pressure	Flow Range	Inlet Sizes	Outlet Sizes
PRU LV 10	0.69 bar	8.62 bar	up to 22713 L/hr	2" F NPT, 2" F BSPT	2" F NPT, 2" F BSPT
PRU LV 15	1.03 bar	8.62 bar	up to 22713 L/hr	2" F NPT, 2" F BSPT	2" F NPT, 2" F BSPT
PRU LV 20	1.38 bar	8.62 bar	up to 22713 L/hr	2" F NPT, 2" F BSPT	2" F NPT, 2" F BSPT
PRU LV 25	1.72 bar	8.62 bar	up to 22713 L/hr	2" F NPT, 2" F BSPT	2" F NPT, 2" F BSPT
PRU LV 30	2.07 bar	8.62 bar	up to 22713 L/hr	2" F NPT, 2" F BSPT	2" F NPT, 2" F BSPT
PRU LV 40	2.76 bar	8.62 bar	up to 22713 L/hr	2" F NPT, 2" F BSPT	2" F NPT, 2" F BSPT
PRU LV 50	3.45 bar	8.62 bar	up to 22713 L/hr	2" F NPT, 2" F BSPT	2" F NPT, 2" F BSPT
PRU LV 60	4.14 bar	8.62 bar	up to 22713 L/hr	2" F NPT, 2" F BSPT	2" F NPT, 2" F BSPT

The PRU-LV limits downstream pressure to no more than 1.03 bar above regulated pressure during static (no flow) conditions.

Recommended for outdoor use only. Not NSF certified.

PRLV MODELS	Preset Outlet Pressure	Maximum Inlet Pressure	Maximum Flow	Inlet Sizes	Outlet Sizes
PRLV10	0.69 bar	8.62 bar	4088 L/hr	3/4" F NPT, 1" F NPT	3/4" F NPT, 1" F NPT
PRLV15	1.03 bar	8.62 bar	4088 L/hr	3/4" F NPT, 1" F NPT	3/4" F NPT, 1" F NPT
PRLV20	1.38 bar	8.62 bar	4088 L/hr	3/4" F NPT, 1" F NPT	3/4" F NPT, 1" F NPT
PRLV30	2.07 bar	8.62 bar	4088 L/hr	3/4" F NPT, 1" F NPT	3/4" F NPT, 1" F NPT
PRLV40	2.76 bar	8.62 bar	4088 L/hr	3/4" F NPT, 1" F NPT	3/4" F NPT, 1" F NPT
PRLV50	3.45 bar	8.62 bar	4088 L/hr	3/4" F NPT, 1" F NPT	3/4" F NPT, 1" F NPT
PRLV60	4.14 bar	8.62 bar	4088 L/hr	3/4" F NPT, 1" F NPT	3/4" F NPT, 1" F NPT

The PRLV limits downstream pressure to no more than 15 psi (1.03 bar) above regulated pressure during static (no flow) conditions.

Recommended for outdoor use only. Not NSF certified.

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

https://www.hunterirrigation.com/en-metric/irrigation-product/pressure-regulators/senningerr-pressure-regulators/pru-lv
091226