Gocciolatori

La giusta quantità di acqua, direttamente alla pianta

VANTAGGI PRINCIPALI

- Compensazione della pressione
- Codifica a colori in base alla portata
- Tre varianti di inserzione: innesto da 6 mm, filettatura da 10-32, FTP da ½"
- Bordi conici per facilitare la presa
- Innesto auto-perforante
- Tappo diffusore opzionale
- Diaframma autopulente
- Periodo di garanzia: 2 anni

Caratteristiche di funzionamento

- Intervallo di pressione consigliato: da 1,4 a 3,5 bar; da 140 a 350 kPa
- Filtrazione minima: 150 mesh; 100 micron

Grafico modello gocciolatore

		Modello	Tipi di ingresso	Portata (l/ora)
	Blu	HE-050-B	Innesto autoperforante	2,0
	Nero	HE-10-B	Innesto autoperforante	4,0
	Rosso	HE-20-B	Innesto autoperforante	8,0
	Marrone chiaro	HE-40-B	Innesto autoperforante	15,0
	Arancione	HE-60-B	Innesto autoperforante	23,0
	Blu	HE-050-T	Filettatura da $^{10}/_{32}$	2,0

	Nero	HE-10-T	Filettatura da $^{10}/_{32}$	4,0
	Rosso	HE-20-T	Filettatura da $^{10}/_{32}$	8,0
	Marrone chiaro	HE-40-T	Filettatura da $^{10}/_{32}$	15,0
	Arancione	HE-60-T	Filettatura da $^{10}/_{32}$	23,0
	Blu	HEB-05	Filettatura femmina da ½"	2,0
	Blu	HEB-05-CV	Filettatura femmina da ½"	2,0

	Nero	HEB-10	Filettatura femmina da ½"	4,0
	Nero	HEB-10-CV	Filettatura femmina da ½"	4,0
	Rosso	HEB-20	Filettatura femmina da ½"	8,0
	Rosso	HEB-20-CV	Filettatura femmina da ½"	8,0
	Marrone chiaro	HEB-40	Filettatura femmina da ½"	15,0
	Marrone chiaro	HEB-40-CV	Filettatura femmina da ½"	15,0

	Arancione	HEB-60	Filettatura femmina da ½"	23,0
	Arancione	HEB-60-CV	Filettatura femmina da ½"	23,0

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

https://www.hunterirrigation.com/it/irrigation-product/micro-irrigation/gocciolatori
090626