

# HC Flow Meter

Detect, monitor, and report critical flow zone data and total system flows with this robust and simple-to-install flow sensor. Add wireless flow-monitoring capabilities to Hydrawise® Systems with a simple and affordable communication kit.

## KEY BENEFITS

- Compatible with HC, HPC, Pro-HC, and HCC Controllers
- Compatible with ICC2 Controller via Centralus™ communication modules
- Flow Rate: 0.22 to 132 GPM (depending on size)
- Provides station-level flow rates and totals in Hydrawise Software
- Sends automatic alerts in the event of high-flow, low-flow, or unscheduled flow conditions
- Flow reports within Hydrawise Software can display total system water use and individual station water use for accurate water budgeting and tracking
- Robust brass construction with union fittings for easy installation and removal for winterization
- Analog dial on the face of the meter displays daily flow totals and a leak detector
- Optional wireless communication kit available for use with any HC Flow Meter and Hydrawise-enabled HC, HPC, Pro-HC, or HCC Controllers



## HC FLOW METER SPECIFICATIONS

	<b>HC-075-FLOW (¾")</b>	<b>HC-100-FLOW (1")</b>	<b>HC-150-FLOW (1½")</b>	<b>HC-200-FLOW (2")</b>
Minimum flow (GPM)	0.22	0.3	0.88	1.98
Maximum recommended flow (GPM)	15	30	66	105
Maximum flow rate (GPM)	21	34	88	132
Dial reading (U.S. gal)	1 pulse per 0.1 U.S. gal	1 pulse per 1 U.S. gal	1 pulse per 1 U.S. gal	1 pulse per 1 U.S. gal
Max working pressure (PSI)	230	230	230	230

## Operating Specifications

- Scaled pulse output is precalibrated from the factory based on the size of the meter
- When wired directly to the controller, meter must be installed with shielded, minimum 18 AWG wire, up to 1,000' from the controller
- Accuracy: ± 2% of reading at recommended flow
- Warranty period: 2 years

## Wireless Operating Specifications

- 500' range (line of sight) from transmitter to receiver
- Communication frequency: 900 MHz for use in North America
- Transmitter power supply: 3 AA batteries
- Receiver power supply: 24 VAC from host controller

## Approvals

- FCC, CE, and RCM approved
- Transmitter is IP68 rated
- Receiver is IP24 rated

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://www.hunterirrigation.com/irrigation-product/sensors/hc-flow-meter>  
061526