Stream Nozzles

The stream nozzles have been replaced by MP Rotator.

OPERATING SPECIFICATIONS

- Recommended operating pressure: 30 PSI
- Pair with Pro-Spray PRS30 pop-up for pressure regulation to 30 PSI
- Warranty period: 2 years

MODEL S-8A STREAM SPRAY NOZZLES PERFORMANCE CHART

Arc	Pressure	Radius	Flow	Precip in/hr	
	PSI	ft	GPM	■	▲
90°	20	7	0.29	2.28	2.63
	25	8	0.32	1.93	2.22
	30	**8**	**0.38**	**2.11**	**2.43**
	35	8	0.41	2.29	2.64
	40	9	0.54	1.95	2.25
180°	20	7	0.54	2.12	2.45
	25	8	0.57	1.71	1.98
	30	**8**	**0.60**	**1.80**	**2.08**
	35	8	0.63	1.89	2.19
	40	9	0.66	1.57	1.81
360°	20	7	1.08	2.12	2.45
	25	8	1.11	1.67	1.93
	30	**8**	**1.15**	**1.73**	**2.00**
	35	8	1.18	1.77	2.05
	40	9	1.22	1.45	1.67

Bold = Recommended pressure

MODEL S-16A STREAM SPRAY NOZZLES PERFORMANCE CHART

Arc	Pressure	Radius	Flow	Precip in/hr	
Blue •	PSI	ft	GPM	■	▲
90°	20	15	0.40	0.68	0.79
	25	16	0.46	0.69	0.80
	30	**16**	**0.50**	**0.75**	**0.87**
	35	17	0.54	0.72	0.83
	40	18	0.57	0.68	0.78
180°	20	15	0.67	0.57	0.66
	25	16	0.80	0.60	0.69
	30	**16**	**0.88**	**0.66**	**0.76**
	35	17	0.97	0.65	0.75
	40	18	1.04	0.62	0.71
360°	20	15	1.19	0.51	0.59
	25	16	1.46	0.55	0.63
	30	**16**	**1.66**	**0.62**	**0.72**
	35	17	1.82	0.61	0.70
	40	18	1.99	0.59	0.68

Bold = Recommended pressure

Adjustable: 25° to 360° • Recommend use of the PRS30 for optimal pressure of 30 PSI

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

https://www.hunterirrigation.com/irrigation-product/stream-nozzles
091226