

1" PGV

Highly versatile, robust irrigation valves for simple installation and serviceability. 100% of Hunter valves are water-tested.

KEY BENEFITS

- External/internal manual bleed allows for quick and easy activation at the valve
- Double-beaded diaphragm seal design ensures leak-free performance
- Captive bonnet screws eliminate the possibility of lost parts during disassembly
- Triple-tool bonnet screws are compatible with standard or Phillips screwdrivers as well as a nut driver
- Encapsulated solenoid with captive plunger used on every Hunter valve provides hassle-free service
- Flow control maximizes efficiency and prolongs the life of the system



User-Installed Options

- Accu Sync® pressure regulation at the valve*
- DC-latching solenoid for battery-powered controllers (P/N 458200)
- Solenoid conduit cover (P/N 464322)

Factory-Installed Options

- LS: Valve without solenoid
- DC: DC-latching solenoid for battery-powered controllers

1" PGV Operating Specifications

- Flow: 0.2 to 40 GPM
- Recommended pressure range: 20 to 150 PSI
- Temperature rating: 150°F
- Warranty period: 2 years

1½" and 2" PGV Operating Specifications

- Flow:
 - PGV-151: 20 to 120 GPM
 - PGV-201: 20 to 150 GPM
- Recommended pressure range: 20 to 150 PSI
- Temperature rating: 150°F
- Warranty period: 2 years
- View more details for [1½" and 2" PGV >](#)

1" PGV Pressure Loss Chart

1" PGV and PGV Jar-Top Pressure Loss in PSI

Flow GPM	1" Globe	1" Angle	1" Male x Male	1" Male x Barb
1	3	1	2	2
5	4	1	2	2
10	4	1	2	2
15	5	1	3	3
20	5	2	4	4
25	6	2	7	6
30	8	3	10	10
40	14	5	18	16

1½" and 2" PGV Pressure Loss Chart

1½" and 2" PGV Pressure Loss in PSI

Flow GPM	1½" Globe	1½" Angle	2" Globe	2" Angle
20	3	3	1	1
30	3	3	1	2
35	3	3	2	2
40	3	3	2	2
50	4	3.5	1	1
60	5	4	2	2
80	5.5	4.5	3	2
100	9	8	5	3
120	11.5	10.5	6	5
135			8	7
150			10	9

Solenoid Specifications

- 24 VAC solenoid
 - 350 mA inrush, 190 mA holding, 60 Hz
 - 370 mA inrush, 210 mA holding, 50 Hz

1" PGV AND PGV JAR-TOP PRESSURE LOSS IN PSI

Flow GPM	1" Globe	1" Angle	1" Male x Male	1" Male x Barb
1	3	1	2	2
5	4	1	2	2
10	4	1	2	2
15	5	1	3	3
20	5	2	4	4
25	6	2	7	6
30	8	3	10	10
40	14	5	18	16

1½" AND 2" PGV PRESSURE LOSS IN PSI

Flow GPM	1½" Globe	1½" Angle	2" Globe	2" Angle
20	3	3	1	1
30	3	3	1	2
35	3	3	2	2
40	3	3	2	2
50	4	3.5	1	1
60	5	4	2	2
80	5.5	4.5	3	2
100	9	8	5	3
120	11.5	10.5	6	5
135			8	7
150			10	9

Copyright © 2025 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://www.hunterirrigation.com/irrigation-product/valves/1-pgv>
020925