

I-40

Radius: **44' to 76'**
Flow: **7.6 to 33.7 GPM**

The I-40 Rotor has a comprehensive list of upgraded features that make it the top choice for demanding, large turf projects.

KEY BENEFITS

- Patented automatic arc return feature returns the turret back to the original arc pattern if vandalized; adjustable arc from 50° to 360°
- Non-strippable drive mechanism is protected from damage if turned in the opposite direction of travel
- Part- and full-circle in one model for flexibility across landscapes and reduced inventory
- Color-coded nozzles make identification easy
- Available opposing nozzle model for even watering in full-circle applications (I-40-ON model)
- Drain Check Valve prevents low-head drainage (up to 15' of elevation)

OPERATING SPECIFICATIONS

- Nozzle choices: 12
- Radius I-40: 44' to 69'
- Radius I-40-ON: 52' to 76'
- Flow I-40: 7.6 to 29.5 GPM
- Flow I-40-ON: 13.0 to 33.7 GPM
- Recommended pressure range: 40 to 100 PSI
- Operating pressure range: 40 to 100 PSI
- Precipitation rate: 0.4 in/hr approximately
- Nozzle trajectory: standard = 25°
- Warranty period: 5 years

FACTORY-INSTALLED OPTIONS

- Reclaimed water ID
- High-speed rotations

USER-INSTALLED OPTIONS

- HSJ-1 prefabricated 1" PVC Swing Joint



I-40-04

Overall height: 7⁷/₈"
Pop-up height: 4"
Exposed diameter: 2"
Inlet size: 1"



I-40-06

Overall height: 10¹/₄"
Pop-up height: 6"
Exposed diameter: 2"
Inlet size: 1"



I-40 Reclaimed

Available as a factory-installed option on all models



I-40 High-Speed

Available as a factory-installed option on all models

I-40 - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1 Model	2 Standard Features	3 Feature Options	4 Nozzle Options
I-40-04-SS = 4" pop-up I-40-06-SS = 6" pop-up	Adjustable arc, stainless steel riser, check valve, and 6 nozzles	(blank) = No option HS = High-speed HS-R = High-speed and reclaimed water ID R = Reclaimed water ID	8 to 25 = Factory-installed nozzle number

I-40-ON - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1 Opposing Nozzle Model	2 Standard Features	3 Feature Options	4 Nozzle Options
I-40-04-SS-ON = 4" pop-up I-40-06-SS-ON = 6" pop-up	Full-circle, opposing nozzle, stainless steel riser, check valve, and 6 nozzles	(blank) = No option HS = High-speed HS-R = High-speed and reclaimed water ID R = Reclaimed water ID	15 to 28 = Factory-installed nozzle number

Examples:

I-40-04-SS = 4" pop-up, adjustable arc, stainless steel riser, with check valve

I-40-04-SS-ON-R-23 = 4" pop-up, adjustable arc, stainless steel riser, with check valve, and reclaimed water ID and 23 nozzle

I-40-06-SS-15 = 6" pop-up, adjustable arc, stainless steel riser, with check valve and 15 nozzle